

Application form for textile testing – fabric



Please download and save the form before clicking on the “SUBMIT” button.

Customer

Address:	Company:	Street, Nr.:	
	Place:	Postcode:	Country:
Contact person:	Name:	Surname:	
	Tel.:	E-Mail:	

Sample information

Product description:
Article number:
Area of application:
Material composition:
Colour:
Binding:

Care labelling:

	Washing	Temperature:	Delicate cycle	
	Bleaching	Do not bleach	Chlorine & oxygen bleaching	Only oxygen bleaching
	Tumble drying	Drying level:	Delicate cycle	
	Ironing	Temperature:		
	Dry cleaning	Method:		

Recommended testing for fabric package *

Fibre analysis:	Various methods (<i>quantitative</i>)	Various methods (<i>qualitative</i>)
Yarn fineness:	EN ISO 2060	
Yarn twist:	EN ISO 2061	
Fabric width:	EN 22198	
Threads per unit length:	EN 1049-2	
Fabric weight:	EN 12127	
Dimensional change:	EN ISO 3759/5077/6330	
Determination of spirality:	ISO 16322-2	

Washing/Drying:	According to laundry symbol With intermediate drying	Other (<i>please specify</i>) Without intermediate drying	No. of washing cycles
Strip method in %:	EN ISO 13934-1		
Tear force:	EN ISO 13937-1	EN ISO 13937-2	EN ISO 13937-3 EN ISO 13937-4
Fabric weight:	EN 12127		
Resistance to water:	DIN EN 20811		
Water repellency:	ISO 29865 (<i>Bundesmann</i>)	EN ISO 4920 (<i>spray test</i>)	
Water vapour resistance:	ISO 11092		
Thermal resistance:	EN ISO 11092		
Permeability to air:	EN ISO 9237		
Martindale abrasion resistance:	EN ISO 12947-2		
Recovery from creasing:	ISO 2313 (<i>crease angle</i>)	ISO 9867 (<i>crease recovery replicates</i>)	
Smoothness appearance:	EN 7768		
Pilling resistance:	EN ISO 12945-1 (<i>Pilling-Box</i>)	EN ISO 12945-2 (<i>Martindale Method</i>)	
Snagging resistance:	BS 8479 (<i>Snag Pod</i>)	ASTM D3939/D3939M – 13 (<i>ProMace</i>)	
Colour fastness to washing:	EN ISO 105-C06	EN ISO 105-C08	EN ISO 105-C09
Colour fastness to ironing:	EN ISO 105-X11		
Colour fastness to light/weathering:	EN ISO 105-B02	EN ISO 105-B04	
Colour fastness to perspiration:	EN ISO 105-E04		
Colour fastness to rubbing (dry/wet):	EN ISO 105-X12		
Colour fastness to water:	EN ISO 105-E01		

*All testing is carried out according to current standards.

Proven Quality label

The Proven Quality label and hangtag offer a high level of credibility to the consumer. If you are interested please tick the box.



Other:

Remarks:

If the „SUBMIT“ button does not work you can send the form as an attachment by e-mail to: technology_customer_requests@testex.com.